




PUMP SPECS



MODEL

M-3425-ML or -AL

M-3425CS-PO

PART NUMBER

133260-01 w/manual nozzle
133260-02 w/auto nozzle

133262-04
(Pump only model)

VOLTAGE & TYPE

24-Volt DC - Vane

24-Volt DC - Vane

FLOWRATE

Up to 25 GPM (95 LPM)

Up to 25 GPM (95 LPM)

DUTY CYCLE

30 min. On / 30 min. Off

30 min. On / 30 min. Off

POWER CORD

15 ft. (4.6m) of 10/3 AWG

15 ft. (4.6m) of 10/3 AWG

NOZZLE

Choice of manual or
automatic shutoff.

None

SUCTION PIPE

None

None

HOSE

12 ft. (3.7m) x 1 in.

None

MOTOR PROTECTION

20 amp circuit breaker

20 amp circuit breaker

UNIQUE FEATURE

Highest flow, 24-volt pump,
reduces time spent
refueling.

Weight centering
inlet base - includes
check valve.

USE WITH

Gasoline (alcohol blends E15),
diesel fuel (biodiesel blends
B20) and kerosene.

Gasoline (alcohol blends E15),
diesel fuel (biodiesel blends
B20) and kerosene.

APPROVALS

Motor is U.L. Listed to
U.S. and Canadian Standards

Motor is U.L. Listed to
U.S. and Canadian Standards

WARRANTY

2 Year

2 Year