










## FILL CAPS & ADAPTORS

		MODEL #	PREFERRED
<p style="text-align: center;"><b>Vented Fill Cap</b></p> <div style="display: flex; justify-content: space-around;">   </div> <p style="text-align: center;"><b>179</b>                      <b>179M</b></p> <p>Loose-seal style cap with hinged cover for fill port of small storage tanks. Lockable with a padlock. Aluminum or cast iron. Available with male and female threads.</p>		<b>09-179-0100</b> 2" Female	<b>\$ 20.84</b>
		<b>09-179-0300</b> 3" Female	<b>\$ 46.75</b>
		<b>09-179-0400</b> 4" Female	<b>\$ 60.52</b>
		<b>09-179CI-0100</b> 2" Female Cast Iron	<b>\$ 47.69</b>
		<b>09-179M-0100</b> 2" Male	<b>\$ 22.61</b>
		<b>09-179MCI-0100</b> 2" Male Cast Iron	<b>\$ 45.08</b>
 <p style="text-align: center;"><b>Pre-Vent Fill Cap</b> Combination Vent &amp; Fill 2" Male NPT</p>	<b>03-60001</b> PREVENT FILL CAP	<b>\$ 21.79</b>	
		<b>03-60003</b> REPLACEMENT TOP	<b>\$ 12.18</b>
 <p style="text-align: center;"><b>305</b> <b>Fill Adaptor</b></p> <p>Adaptor is profile machined for cam and groove fit on industry standard tight seal caps.</p>	<b>09-305-0000</b> 2"	<b>\$ 63.64</b>	
		<b>09-305-0200</b> 4"	<b>\$ 75.88</b>
 <p style="text-align: center;"><b>305 C Fill Cap</b></p> <p>4" Cap has center pull ring with toggle cam to fit adaptor groove. Tight seal and lockable. Powder-coat finish. 2" Cap has a single lever.</p>	<b>09-305C-2000</b> 2"	<b>\$ 54.13</b>	
		<b>09-305C-0100</b> 4"	<b>\$ 57.88</b>
 <p style="text-align: center;"><b>Vapor Recovery</b></p> <p>Installed on Vapor Adaptors and Vapor Swivel Adaptors to prevent water and debris from entering the tank and prevent vapor from escaping when the adaptors are not in use. The cap has a tight seal and orange powder-coated finish.</p>	<b>09-323C-0100-AC</b> 4"	<b>\$ 62.00</b>	

## VENTS

		MODEL #	PREFERRED
 <p><b>354 Updraft Vent</b></p> <p>“Open” vent used on underground and aboveground tanks for motor fueling. Vent allows tank to “breathe” during filling/dispensing operations.</p>		<b>09-354-0100</b> 1 1/2”	\$ 31.84
		<b>09-354-0200</b> 2”	\$ 27.39
		<b>09-354-0300</b> 3”	\$ 65.16
		<b>09-354-0400</b> 4”	\$ 144.03
		<b>09-155-0200AV</b> 1 ”	\$ 24.78
 <p><b>155 “T” Style Vent</b></p> <p>Aluminum T-style Vent used primarily on small fuel oil storage tanks. Outlet ports on either side of the inlet with 20 mesh stainless steel screen keeps debris out of the airway.</p>		<b>09-155-0400AV</b> 1 1/2”	\$ 31.54
		<b>09-155-0500AV</b> 2”	\$ 37.94
		<b>51-4021</b> 3/4”	\$ 12.62
 <p><b>Mushroom Vent Caps</b></p> <p>Rust-resistant galvanized cast iron design is available in female NPT sizes from 3/4” to 4” Each cap is designed with a 30 mesh screen, to prevent debris from entering the vent pipe.</p>		<b>51-4022</b> 1”	\$ 16.37
		<b>51-4023</b> 1 1/4”	\$ 18.63
		<b>51-4024</b> 1 1/2”	\$ 22.64
		<b>51-4025</b> 2”	\$ 32.04
		<b>51-4027</b> 3”	\$ 101.95
		<b>51-4028</b> 4”	\$ 119.01

## ANTI-SYPHON VALVES



  <p><b>Anti-Syphon Valve</b></p> <ul style="list-style-type: none"> <li>-Thermal Expansion pressure relief valve</li> <li>-Automatically Shuts Flow Off When Lines are Broken</li> <li>-Each Valve has an Adjustable Head Pressure</li> </ul>	5' TO 12' HEAD PRESSURE	<b>26-605-300-01</b> 3/4”	\$ 516.89
		<b>26-606-300-01</b> 1”	\$ 530.86
		<b>26-616-300-01</b> 1 1/2”	\$ 548.64
		<b>26-636-300-11</b> 2”	\$ 631.19
	12' TO 25' HEAD PRESSURE	<b>26-616-300-02</b> 1 1/2”	\$ 548.64
		<b>26-636-300-12</b> 2”	\$ 631.19

**MORRISON EMERGENCY VENTS**

		MODEL #	PREFERRED
<p><b>244OM SERIES MALE THREADED CAST IRON E-VENTS</b></p>  <p>Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.</p>		<b>09-244OM-0020AV</b> 2" MALE THREAD	\$ 86.46
		<b>09-244OM-0050AV</b> 3" MALE THREAD	\$ 110.45
		<b>09-244OM-0100AV</b> 4" MALE THREAD	\$ 130.84
		<b>09-244OM-0800AV</b> 5" MALE THREAD	\$ 186.15
		<b>09-244OM-0200AV</b> 6" MALE THREAD	\$ 200.65
<p><b>244O SERIES FEMALE THREADED CAST IRON E-VENTS</b></p>  <p>Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.</p>		<b>09-244O-0100AV</b> 4" FEMALE THREAD	\$ 124.95
		<b>09-244O-0200AV</b> 6" FEMALE THREAD	\$ 182.12
<p><b>245M SERIES MALE THREADED ALUMINUM E-VENTS</b></p>  <p>Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.</p>		<b>09-245M-0300AV</b> 3" MALE THREAD	\$ 87.35
		<b>09-245M-0400AV</b> 4" MALE THREAD	\$ 105.35
		<b>09-245M-0600AV</b> 6" MALE THREAD	\$ 159.89
<p><b>245 SERIES FEMALE THREADED ALUMINUM E-VENTS</b></p>  <p>Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.</p>		<b>09-245-0300AV</b> 3" FEMALE THREAD	\$ 81.54
		<b>09-245-0400AV</b> 4" FEMALE THREAD	\$ 98.48
		<b>09-245-0600AV</b> 6" FEMALE THREAD	\$ 145.06

8" AND 10" E-VENTS AVAILABLE CALL FOR PRICING

**AST SPILL CONTAINERS**

 <p><b>MORRISON 09-517 SPILL CONTAINER</b></p> <p>3.5 GAL AVAILABLE WITH MALE OR FEMALE THREAD</p> <p>Waste Oil Version has screen</p>	MODEL #	PREFERRED
	<p><b>09-517-0100AC</b> 2" 3.5 GAL. MALE THREADED</p>	<p><b>\$ 261.90</b></p>
	<p><b>09-517-0200AC</b> 4" 3.5 GAL. MALE THREADED</p>	<p><b>\$ 288.25</b></p>
	<p><b>09-517F-0100AC</b> 2" 3.5 GAL. FEMALE THREADED</p>	<p><b>\$ 272.97</b></p>
	<p><b>09-517F-0200AC</b> 4" 3.5 GAL. FEMALE THREADED</p>	<p><b>\$ 303.72</b></p>
	<p><b>09-517WO-0100AC</b> 2" 3.5 GAL. FEMALE THREADED W/ SCREEN</p>	<p><b>\$ 280.81</b></p>
 <p><b>MORRISON 09-518 SPILL CONTAINER</b></p> <p>7.5 GAL AVAILABLE WITH MALE OR FEMALE THREAD</p> <p>Available in Center or Offset Mounts</p>	<p><b>09-518-0100AC</b> 4" 7.5 GAL. FEMALE THREADS OFFSET MOUNT</p>	<p><b>\$ 600.20</b></p>
	<p><b>09-518CC-0100AC</b> 4" 7.5 GAL. FEMALE THREADS CENTER MOUNT</p>	<p><b>\$ 600.20</b></p>
	<p><b>09-518M-0100AC</b> 4" 7.5 GAL. MALE THREADS OFFSET MOUNT</p>	<p><b>\$ 600.20</b></p>
	<p><b>09-518M-0200AC</b> 2" 7.5 GAL. MALE THREADS OFFSET MOUNT</p>	<p><b>\$ 576.84</b></p>

**SPILL CONTAINERS**



15 Gallon AST Remote Spill Container

One, or Dual Fill Ports

**MODEL #**

**PREFERRED**

**09-515-0200AC**  
2" 15 GAL FEMALE  
THREADED

**\$ 1,599.34**

**09-515-0300AC**  
3" 15 GAL FEMALE  
THREADED

**\$ 1,646.54**

**09-515-0400AC**  
4" 15 GAL FEMALE  
THREADED

**\$ 1,671.59**

**09-515-2200AC**  
2" & 2" 15 GAL DUAL  
PORTS FEMALE  
THREADED

**\$ 1,696.25**

**09-515-2300AC**  
3" & 3" 15 GAL DUAL  
PORTS FEMALE  
THREADED

**\$ 1,828.17**



EBW SPILL  
CONTAINERS

**26-705-470-01**  
5 GAL SPILL TRAP  
W/ DRAIN

**\$ 1,086.23**

**26-705-409-00**  
ALUMINUM FLEX  
CATCH COVER

**\$ 214.63**



FLEX CATCH  
COVERS





**26-705-423-01**  
FIBER FLEX CATCH  
COVER

**\$ 190.50**


**26-705-430-00**  
CAST IRON FLEX  
CATCH COVER

**\$ 195.58**


**OVERFILL, BY-PASS & PRESSURE RELIEF VALVES**

		MODEL #	PREFERRED
 <p>9095A</p>  <p>9095S</p>		<p><b>09-9095AA-3300AVEVR</b> 3" OVERFILL ADAPTOR</p>	\$ 1,587.11
		<p><b>09-9095AA-0200AV</b> 2" OVERFILL VALVE</p>	\$ 1,347.58
		<p><b>09-9095SA-0200AV</b> 2" OVERFILL VALVE MALE</p>	\$ 691.46
 <p>1/2" EXPANSION RELIEF VALVES</p>		<p><b>09-078DI-0100AV</b> 25 PSI SETTING</p>	\$ 158.57
		<p><b>09-078DI-0200AV</b> 40 PSI SETTING</p>	\$ 158.57
		<p><b>09-078DI-0300AV</b> 100 PSI SETTING</p>	\$ 158.57
 <p><b>09-174 BY-PASS VALVE 1 1/2" OR 2"</b></p>		<p><b>09-174-0100AV</b> 1 1/2" PSI STANDARD SETTING</p>	\$ 432.09
		<p>PRESSURE SETTINGS OF 30,40,50,60 &amp; 75 PSI AVAILABLE AT ADDITIONAL CHARGE</p>	CALL FOR PRICING
		<p><b>09-174-2200AV</b> 2" 20 PSI STANDARD SETTING</p>	\$ 466.35
	<p>PRESSURE SETTINGS OF 30,40,50,60 &amp; 75 PSI AVAILABLE AT ADDITIONAL CHARGE</p>	CALL FOR PRICING	

## TANK GAUGES

 <p><b>Kreuger At-A-Glance Gauges</b></p> <p>Direct mechanical action, reliable construction and "at-a-glance" readability make this gauge a perfect choice for tanks with depths up to 12'.</p> <ul style="list-style-type: none"> <li>- Patented calibration assembly withstands pressure of 70 lbs. per sq. inch.</li> <li>- Double plastic dome is almost indestructible.</li> <li>- "Gallon" readout available for Standard 275 Gallon Oval Tanks.</li> <li>- All "internal tank" parts available in stainless steel or plastic.</li> <li>- Repair parts available.</li> </ul>	Tank Depth	MODEL #	PREFERRED
	27"	12-D-1.5-27 1 1/2"	\$ 34.57
12-D-2-27 2"		\$ 34.57	
38"	12-D-1.5-38 1 1/2"	\$ 34.57	
	12-D-2-38 2"	\$ 34.57	
44"	12-D-1.5-44 1 1/2"	\$ 34.57	
	12-D-2-44 2"	\$ 34.57	
48"	12-D-1.5-48 1 1/2"	\$ 41.61	
	12-D-2-48 2"	\$ 41.61	
60"	12-D-1.5-60 1 1/2"	\$ 41.61	
	12-D-2-60 2"	\$ 41.61	
64"	12-D-1.5-64 1 1/2"	\$ 51.96	
	12-D-2-64 2"	\$ 51.96	
<b>Kreuger At-A-Glance replacement tops</b>		12-DCAL	\$ 8.83
<b>Kreuger At-A-Glance repair kits - includes top, red nut, gasket, indicator disc</b>		12-DKIT	\$ 15.88
<b>Kreuger At-A-Glance Glass insert replacement</b>		12-DG-CAL	\$ 18.23
<b>Kreuger Glass gauge repair kits - include glass insert, red nut &amp; gasket, &amp; red indicator</b>		12-DG-KIT	\$ 23.25

## INTERSTITIAL LEAK GAUGE

 <p><b>Kreuger Leak Gauges</b></p> <p>Vertical type leak monitor used for detecting leaks in the annular/interstitial space of a double wall above ground tank.</p>	Tank Depth	MODEL #	PREFERRED
	UP to 48"	12-K-1.5-48	\$ 72.58
UP to 38"	12-K-2-38	\$ 64.45	
UP to 48"	12-K-2-48	\$ 72.58	
UP to 64"	12-K-2-64	\$ 72.58	
UP to 108"	12-K-2-108	\$ 105.18	
<b>Leak Gauge Top</b>		12-KCAL	\$ 8.83
<b>Leak Gauge Kit</b>		12-KKIT	\$ 18.55

**KRUEGER H TYPE GAUGES & KING GAUGES**

**Krueger Type H Therma Gauges**



The therma Type H gauge is a reliable, swing arm type tank gauge. The difference from an At-A-Glance gauge and Type H gauge is the bushing. This gauge has an easily removable bushing which allows you to thread the bushing into the tank first. This eliminates the swing arm from spinning inside the tank and allows you to aim the swing arm where you want it.

- \* Galvanized Construction
- \* HDPE Floats
- \* Aluminum body

Tank Depth	MODEL #	PREFERRED
30"	12-H-2-30 2"	\$ 39.74
38"	12-H-2-38 2"	\$ 39.74
44"	12-H-1.5-44 1 1/2"	\$ 39.74
	12-H-2-44 2"	\$ 39.74
46"	12-H-2-46 2"	\$ 39.74
48"	12-H-1.5-48 1 1/2"	\$ 47.54
	12-H-2-48 2"	\$ 47.54
60"	12-H-2-60 2"	\$ 47.54
64"	12-H-1.5-64 1 1/2"	\$ 58.86
	12-H-2-64 2"	\$ 58.86

**Type H Therma Gauge replacement top**

12-HCAL \$ 8.83

**Krueger Type H repair kits - includes top, red lock nut, gasket & indicator disc**

12-HKIT \$ 16.93

**Krueger At-A-Glance Alarm**



Loud Audible alarm (102 dB)  
Easy installation  
Set for high level, low level or leak detection alarm Lithium battery  
Can add on to existing gauges  
Weather resistant convenient reset switch

12-DALARM \$ 144.00

**King Gauges**



The King gauge is made entirely of rustproof materials. Resin treated float is unaffected by oil or moisture condensation and simple lever action assures trouble free operation. Gauge has 1 1/2" and 2" threads for versatile use with any size tank opening.






51-4504 44"	\$ 37.44
51-4490A-38 38"	\$ 48.67
51-4490A-48 48"	\$ 48.67
51-4490A-64 64"	\$ 48.67

**King Gauge Top w/ Gasket**

51-4495 \$ 6.79



## VENT ALARMS & GAUGES

<b>VENT ALARMS &amp; GAUGES</b>		<b>MODEL #</b>	<b>PREFERRED</b>
 <p style="text-align: center;"><b>KING COMBINATION ALARM/GAUGE</b></p> <p>Nitrophyl Float is impervious to petroleum products Tangle-Free "Solid Link" hinge withstands rough handling. Durable cast iron with corrosion-resistant powder coating. Available to fit both Vertical and Horizontal tank applications. Large, easy-to-read, plastic vile includes UV inhibitors and is break-resistant.</p> <p>First size indicates bottom thread size Second size indicates top thread size</p>		<b>51-4522</b> 1 1/2" x 1 1/4"	<b>\$ 56.24</b>
		<b>51-4523</b> 2" x 1 1/4"	<b>\$ 56.24</b>
		<b>51-4524</b> 1 1/2" x 1 1/2"	<b>\$ 56.24</b>
		<b>51-4525</b> 2" x 1 1/2"	<b>\$ 56.24</b>
		<b>51-4526</b> 2" x 2"	<b>\$ 66.16</b>
		<b>Horizontal</b> <b>51-4531</b> 1 1/2" x 1 1/2"	<b>\$ 56.24</b>
<p style="text-align: center;"><b>KING FILL ALARMS</b></p> <p>Sizes to fit most popular above-ground and in-ground tanks Durable cast iron with corrosion-resistant powder coating Whistles while tank is being filled; stops whistling when oil has reached safe capacity level.</p>   <p style="text-align: center;">Industry's widest range of male and female NPT sizes. Available in sizes from 1 1/4" x 1" to 2" x 2"</p> <p>Compression and Union Fill Alarms also available</p> <p>First size indicates bottom thread size Second size indicates top thread size</p>		<b>51-4509</b> 1 1/4" x 1 1/4"	<b>\$ 34.74</b>
		<b>51-4511</b> 1 1/2" x 1 1/4"	<b>\$ 34.74</b>
		<b>51-4512</b> 1 1/2" x 1 1/2"	<b>\$ 34.74</b>
		<b>51-4514</b> 2" x 1 1/4"	<b>\$ 34.74</b>
		<b>51-4515</b> 2" x 1 1/2"	<b>\$ 34.74</b>
		<b>51-4517</b> 2" x 2"	<b>\$ 62.51</b>
 <p style="text-align: center;"><b>Morrison Bros. Co.</b> <small>Established 1855</small></p> <p>For Measuring liquid level in aboveground storage tanks. Gauge mounts on top of tank and is activated by a float connected to a cable. Read-out is on a 1 hour clock face. Small hand=feet, Large hand=inches. Gauge can be read 20-30 feet away. Maximum measurement is 12 feet.</p> <p style="text-align: center;"><b>818</b> <b>Clock Gauge</b></p>		<b>09-818-0100AGEVR</b>  <b>Clock Gauge</b>	<b>\$ 618.74</b>
 <p>Utilizes the 818 clock gauge with a built-in high level warning alarm. Contains a battery powered, intrinsically safe alarm unit that is mounted in a remote location. Alarm level is set during installation and can be reset at any time.</p> <p style="text-align: center;"><b>918</b> <b>Clock Gauge</b></p>		<b>09-918C-0100AG</b>  <b>Clock Gauge w/ Alarm</b>	<b>\$ 1,391.76</b>

## OPW TANK GAUGES

### OPW 200TG TANK GAUGE

The OPW200TG tank gauge is designed for reading liquid levels in horizontal vertical aboveground storage tanks. It provides an accurate numerical counter readout, eliminating the need for any on-site manual gauging. Fits up to a 40' tank. UL Listed.



### FEATURES:

- \* **Vapor Tight:** Allows for standard tank pressure testing, sealing up to 25 PSIG.
- \* **Angled Face:** Improves visibility from ground on large diameter tanks. May be read easily up to 30' away.
- \* **Swivel Adaptor Base:** Allows 360° gauge face rotation for easy viewing wherever needed.
- \* **Easy Installation:** 2" NPT threaded base reduces labor time and comes standard with female thread. A 200-0202 may be purchased for male thread applications.
- \* **Corrosion-Resistant Construction:** A powder coated die-cast aluminum body ensures long service life in many fluids.
- \* **Float Buoyancy:** Designed to float in all fluids with a specific gravity of 0.65 or greater.
- \* **Unit Measurement:** Can be purchased in metric units to read in meters, 1/10, 1/100, or english units to read in feet and inches accurate to 1/8'.
- \* **Maintenance:** No annual maintenance required.
- \* **Tank Size:** Available in either 18' or 40' tank depths.
- \* **Drop Tube:** Prevents float entanglement in the tank and gives the gauge a more accurate reading when turbulence is present. **(SOLD SEPARATELY).**

MODEL #	PREFERRED
28-200TG-ENG18 UP to 18'	\$ 761.45
28-200TG-ENG40 UP to 40'	\$ 898.52

### OPW 144TA LIQUID LEVEL TANK ALARM

The 144TA Tank Alarm is designed for one tank. The 444TA is designed for four tanks. Both have high or low liquid level sensing in liquid tanks. Both audio and visual indicators are used to ensure reliable notifications. Both the 144TA and the 444TA require the 44TA-LLFS liquid level float switch.



### FEATURES:

- \* **Long Life Lithium Battery:** Self powered by a Lithium battery; includes a 10 year shelf life to ensure peace of mind for the owner.
- \* **Visual Notifications:** Red alarm light flash during use for notification to the user. Low battery light indicates when battery needs replacing.
- \* **Audible Alarm:** Sounds a 90 decible alarm at 4' away to meet OSHA requirements.
- \* **Active from the time it leaves the factory:** There is no on/off switch to deal with which means no drained batteries and operator error are eliminated.
- \* **Stainless Steel Pipe Construction:** Allows use in any array of fluid applications.
- \* **Easy Installation:** Requires no calibration and installs easily into a 1" bung.
- \* **Cold Weather Applicable:** All components are rated for -40°F operation.

MODEL #	PREFERRED
28-144TA-0100	\$ 727.84
28-444TA-0100	\$ 1,097.63
28-44TA-LLFS	\$ 338.74

SWING CHECK VALVES, EXTERNAL EMERGENCY VALVES, IMPACT VALVES, & PRESSURE REGULATOR VALVES					
<b>SWING CHECK VALVES</b>		<b>MODEL #</b>	<b>PREFERRED</b>		
 <p><b>DIXON SWCV</b> Swing Check Valve Brass</p>	 <p><b>MORRISON 246A</b> Swing Check Valve Body - Brass Gasket - Nitrile</p>	06-SWCV50	1/2"	\$ 18.10	
		06-SWCV75	3/4"	\$ 23.10	
		06-SWCV100	1"	\$ 31.45	
		06-SWCV125	1 1/4"	\$ 52.99	
		09-246A-0100AV	1 1/2"	\$ 285.24	
		09-246A-0200AV	2"	\$ 300.31	
		09-246A-0400AV	3"	\$ 520.65	
		<b>FARM TANK EMERGENCY VALVES</b>			
 <p><b>Farm Tank Emergency Valve</b> Angle Style, Furnished with 160* fusible link. All brass construction.</p>	09-474-0100	1" x 3/4" NPT	\$ 94.57		
	09-474-0200	1" x 1" NPT	\$ 94.22		
 <p><b>Farm Tank Emergency Valve</b> Straight Style, Furnished with 160* fusible link. All brass construction.</p>	09-574-0100AV	1" x 1" NPT	\$ 113.73		
<b>DUPLEX &amp; DOUBLE TAPPED BUSHINGS</b>					
<b>DOUBLE TAPPED BUSHINGS</b>		09-184-0200	2" x 1/2"	\$ 17.90	
 <p>Cast Iron with NPT Threads</p> <p>Other Sizes Available</p>	09-184-0300	2" x 3/4"	\$ 18.08		
	09-184-0400	2" x 1"	\$ 18.08		
	09-184-0600	2" x 1 1/2"	\$ 18.41		
	09-184-1200	3" x 1 1/2"	\$ 71.88		
	09-184-1400	3" x 2"	\$ 23.52		
	09-184-2400	4" x 1 1/2"	\$ 35.77		
	09-184-2500	4" x 2"	\$ 27.25		
	<b>DUPLEX BUSHINGS</b>		09-184D-0100	2"x3/8"x3/8"	\$ 38.29
	 <p>2" Male NPT for aboveground or underground installations. Fittings available for 3/8", 1/2" copper tubing.</p>	09-184D-0200	2"x1/2"x1/2"	\$ 41.46	
09-184D-0300AB		4"x3/4"x3/4"	\$ 131.04		

LOCKABLE  
**GATE, BALL, AND SOLENOID VALVES**

**Lockable & Non-Lockable Gate Valves**



Rising Stem Gate Valve used for manual flow control in petro-chemical liquid handling. Available in brass and ductile iron. This gate valve operates by rotating handwheel counter-clockwise to open or clockwise to close. Valve can be left partially open to control flow rate. Cold non-shock pressure limit of 200 psi. Available with standard Buna seals or with Teflon seals.

NON-LOCKABLE	MODEL #	PREFERRED
	09-235-0200 2"	\$ 438.40
09-235-0400 3"	\$ 648.16	
09-235B-0200 2"	\$ 507.15	
09-235B-0400 3"	\$ 735.10	



**FULL PORT BALL VALVES**

Full port ball valve used for liquid handling with manual open-close in quick quarter-turn handle operation. Threaded (NPT) connections. Valve can be operated in partial or open position. B0series is Lockable with padlock.

NON-LOCKABLE	09-691-0300 1/2" Std	\$ 16.16
	09-691-0400 3/4" Std	\$ 23.04
	09-691-0500 1" Std	\$ 37.64
	09-691-0700 1 1/2" Std	\$ 73.91
	09-691-0800 2" Std	\$ 121.71
	09-691-1000 3" Std	\$ 466.22
LOCKABLE	09-691B-0300 1/2" Lockable	\$ 20.97
	09-691B-0400 Lockable	\$ 28.37
	09-691B-0500 1" Lockable	\$ 42.99
	09-691B-0700 1 1/2" Lockable	\$ 79.77
	09-691B-0800 2" Lockable	\$ 127.56
	09-691B-1000 3" Lockable	\$ 482.90







**Solenoid Valves**

- Explosion Proof
- 110 Volt
- Used to prevent accidental siphoning
- 2 way, 1 directional
- Normally closed

09-710-0075 3/4"	\$ 689.31
09-710-0100 1"	\$ 887.13
09-710-0150 1 1/2"	\$ 1,088.81
09-710-0200 2"	\$ 1,329.45
09-710-0300 3"	\$ 3,668.52

## LINE STRAINERS

<b>LINE STRAINERS</b>		<b>MODEL #</b>	<b>PREFERRED</b>
<p style="text-align: center;"><b>CAST IRON Y LINE STRAINER</b></p>  <p>Cast iron body, female x female NPT ends, 304 stainless steel strainer, graphite gasket, 400 PSI WOG, 200 PSI working steam pressure.</p>		<b>06-Y004</b> 3/4"	<b>\$ 63.26</b>
		<b>06-Y005</b> 2"	<b>\$ 78.91</b>
		<b>06-Y006</b> 1 1/4"	<b>\$ 111.76</b>
		<b>06-Y007</b> 1 1/2"	<b>\$ 137.62</b>
		<b>06-Y008</b> 2"	<b>\$ 206.52</b>
<p style="text-align: center;"><b>285 Bottom Clean Out Y Strainer</b></p>  <p>Bottom Clean-Out Y-type strainer used in pipelines to filter debris from flowing into and damaging equipment such as a pump or a meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the bottom. Cast iron body and cap, malleable iron yolk, 304 stainless strainer. Threaded (NPT) connections. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.</p>		<b>09-285</b> 1 1/2" <b>THREADED</b>	<b>\$ 161.39</b>
		<b>09-285</b> 2" <b>THREADED</b>	<b>\$ 196.63</b>
		<b>09-285</b> 3" <b>THREADED</b>	<b>\$ 323.74</b>
<p style="text-align: center;"><b>285FDI Bottom Clean Out Y Strainer</b></p>  <p>Bottom Clean-Out Y-type strainer used in pipelines to filter debris from flowing into and damaging equipment such as a pump or a meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the bottom. Has a 150# raised flanged connections, ductile iron body and cap. Companion flanges available. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.</p>		<b>09-285FDI</b> 3" <b>FLANGED</b>	<b>\$ 903.41</b>
<p style="text-align: center;"><b>286 Top Clean Out Line Strainer</b></p>  <p>Top Clean-Out Y-type strainers are used in pipeline to filter out debris from flowing into and damaging equipment such as a pump or meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the top. Cast iron body and cap malleable iron yolk. Threaded (NPT) connections. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.</p>		<b>09-286</b> 2" <b>THREADED</b>	<b>\$ 348.91</b>
		<b>09-286</b> 3" <b>THREADED</b>	<b>\$ 622.25</b>
		<b>09-286FDI</b> 3" <b>FLANGED</b>	<b>\$ 1,122.27</b>

## BARREL FAUCETS & ACCESSORIES

		MODEL #	PREFERRED
 <p><b>Oil &amp; Molasses Valves</b> For Heavy Oils or Liquids Body - Iron Gate - Brass</p>		<b>09-215A-0100</b> 3/4" NPT	\$ 53.63
		<b>09-215A-0500</b> 2" NPT	\$ 77.60
 <p><b>Quick Closing Barrel Faucets</b> Available in 3/4" or 1" Male NPT Standard Disc is Buna; Teflon and Viton available at additional charge.</p>		<b>09-110-0200</b> 3/4" NPT	\$ 120.03
		<b>09-110-0300</b> 1" NPT	\$ 138.44
 <p><b>Barrel Faucet Ball Valve Type</b> Straight Style Quarter Turn All Brass Body</p>		<b>09-633-0500</b> 1" x 1" NPT	\$ 61.22
 <p><b>Barrel Faucets Ball Valve Type</b> Faucet Style Quarter Turn All Brass Body</p>		<b>09-699F-0400</b> 3/4" X 3/4" NPT	\$ 52.97
		<b>09-699F-0500</b> 1" X 1" NPT	\$ 74.38
 <p><b>Bung Faucets</b> Plastic Bung Faucets for 3/4" &amp; 2" NPT bung openings.</p>		<b>15-ZE68SP</b> 3/4" NPT	\$ 8.38
		<b>15-ZE67</b> 2" NPT	\$ 21.55
 <p><b>Barrel Faucet</b> Die-cast metal bung faucet for 3/4" NPT bung opening in steel drums or barrels. Self-closing. Has hole for padlock.</p>		<b>15-ZE81</b> 3/4" NPT	\$ 13.42
 <p><b>Brass Drum Vent</b> 2" NPT. For petroleum based applications.</p>		<b>15-ZE830</b>	\$ 37.75
 <p><b>Plug Wrench</b> Non-Sparking aluminum wrench for use with 2" and 3/4" drums.</p>		<b>15-ZE169</b>	\$ 16.94



*Leaders in Fluid Handling Solutions*

*Toll Free: 1-877-737-4690*

*[www.strickequipment.com](http://www.strickequipment.com)*

**F 15**

**NOTES**

**PLEASE USE THIS PAGE TO KEEP TRACK OF YOUR MOST POPULAR ITEMS ORDERED AND THEIR PART NUMBERS**

A large, empty rectangular box with a black border, intended for handwritten notes.