


LOADING ARMS, ACCESSORIES & REPAIR KITS











Strick Equipment is a Distributor for OPW Loading Arms, Accessories and Repair Kits. Please call the office at 1-877-737-4690 for assistance in ordering any of these items for your Bulk Plant application.

RHINO TUFF TANKS





Rhino Tuff Tanks are available in several sizes of Gravity Feed or Pump systems. Please call the office at 1-877-737-4690, and we will email you a mini catalog with descriptions and prices.

SWIVEL JOINTS


		MODEL #	PREFERRED	
<p>OPW Swivel Joints All Shown as 3600 series Cast Aluminum, except Styles 10 and 80 Female NPT both ends</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>Style 10 3 Planes of Rotation (not Available in Aluminum)</p> </div> <div style="text-align: center;">  <p>Style 20 1 Plane of Rotation</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;">  <p>Style 30,34,35 1 Plane of Rotation</p> </div> <div style="text-align: center;">  <p>Style 40,44,45 1 Plane of Rotation</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;">  <p>Style 50,56,58 2 Planes of Rotation</p> </div> <div style="text-align: center;">  <p>Style 60 2 Planes of Rotation</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="text-align: center;">  <p>Style 70,76,78 2 Planes of Rotation</p> </div> <div style="text-align: center;">  <p>Style 80 3 Planes of Rotation (not Available in Aluminum)</p> </div> </div> <p>All swivels shown above are the 3600 aluminum series. Repair kits are available for all OPW swivels. Contact us for pricing</p> <p>OPW Engineered Systems fabricated and cast ball bearing swivel joints offer many outstanding features that contribute to their dependability and long life. Quality construction standards include precision machining and 100% penetration welding by certified welders. OPW swivel joints allow you to construct a metal piping system that is moveable, flexible and reliable.</p> <p>Also available in stainless steel, carbon steel, cast bronze and ductile iron. Call for details!</p>		Style 20	1 1/2" 27-3620-0151	\$ 210.32
		Style 20	2" 27-3620-0201	\$ 313.65
		Style 20	3" 27-3620-0301	\$ 397.80
		Style 20	4" 27-3620-0401	\$ 494.16
		Style 30	1 1/2" 27-3630-0151	\$ 248.29
		Style 30	2" 27-3630-0201	\$ 335.61
		Style 30	3" 27-3630-0301	\$ 431.28
		Style 30	4" 27-3630-0401	\$ 511.84
		Style 40	1 1/2" 27-3640-0151	\$ 299.68
		Style 40	2" 27-3640-0201	\$ 313.65
		Style 40	3" 27-3640-0301	\$ 502.20
		Style 40	4" 27-3640-0401	\$ 624.99
Style 50	1 1/2" 27-3650-0151	\$ 451.28		
Style 50	2" 27-3650-0201	\$ 554.20		
Style 50	3" 27-3650-0301	\$ 712.50		
Style 50	4" 27-3650-0401	\$ 1,042.24		
Style 60	1 1/2" 27-3660-0151	\$ 403.10		
Style 60	2" 27-3660-0201	\$ 576.37		
Style 60	3" 27-3660-0301	\$ 679.64		
Style 60	4" 27-3660-0401	\$ 926.43		
Style 70	1 1/2" 27-3670-0151	\$ 498.58		
Style 70	2" 27-3670-0201	\$ 576.37		
Style 70	3" 27-3670-0301	\$ 777.92		
Style 70	4" 27-3670-0401	\$ 1,151.85		

GORMAN-RUPP PUMPS

GORMAN-RUPP "O" SERIES PUMPS



GORMAN-RUPP ROTO-PRIME PUMPS






Strick Equipment is a Distributor for Gorman-Rupp Pumps. Several models and sizes available. Please call 1-877-737-4690 for pricing and availability.

TCS BULK PLANT METERS




Strick Equipment is a Distributor for TCS Bulk Plant Meters. Several models and sizes available. Please call the office at 1-877-737-4690 for pricing and availability.

DECKO PUMPS AND IMPELLERS

 <p>Decko Pump This is the original Simer impeller pump used for years in the petroleum industry to transfer fuel or water from small tanks and sumps. It can be easily mounted on a channel iron or wooden base using a 2 piece coupling and a foot mounted motor. The pump is available in 3/4" (BP20X) or 1" (BP21X) with the X signifying an impeller suitable for fuel.</p>	MODEL #	PREFERRED
	<p>52-BP20X 3/4" Up to 15 GPM</p>	<p>\$ 258.29</p>
	<p>52-BP21X 1" Up to 28 GPM</p>	<p>\$ 338.18</p>
 <p>Decko Impeller Kits Kit includes impeller, shaft and body gasket. 52-53X fits BP20X, 52-63X fits BP21X</p>	<p>52-53X</p>	<p>\$ 56.59</p>
	<p>52-63X</p>	<p>\$ 71.72</p>
 <p>Decko "The Bull Dog" The Bull Gog incorporates a Simer impeller pump with 1/2 HP GE commercial grade motor, 8' grounded power cord, base, coupling and guard for a system that is easy to carry and quick to set up. Just add quick couplers and 1" suction and discharge hoses. The Bull Dog is capable of up to 28 GPM and can handle most corrosive and flammable liquids, as well as water up to 180*</p>	<p>52-90000 Non-explosion Proof</p>	<p>\$ 1,144.93</p>
	<p>52-91000 Explosion Proof</p>	<p>\$ 1,958.53</p>

GORMAN-RUPP "O" SERIES PUMP

<p>Electric Motor Driven Self-Priming Centrifugal Pump</p>	MODEL #	PREFERRED
 <p>Pump Specifications: Size: 2" x 2" NPT - Female Pump casing: Max. operating pressure 28 psi. Enclosed type, five vane impeller: Handles 11/32" diameter spherical solids Seal: Type 21, mechanical, self-lubricated. Carbon rotating face. Ni-resist stationary face. Fluorocarbon elastomers (viton or equivalent). Stainless steel type 18-8 cage and spring. Max temperature of liquid pumped, 160°F.</p> <p>.75 H.P. Motor Specifications Type: Explosion Proof Frame Size: 56 Electrical: -Single Phase; 115V/230V, 60 HZ, 11/5.5 approx. full load amps. -Three phase; 230V/460V, 60 Hz, 230V/460V, 60 Hz, 3.21/1.6 approx full load amps. RPM: 3450</p> <p>2 H.P. Motor Specifications Type: Explosion Proof Frame Size: 56 Electrical: -Single Phase; 115V/230V, 60 HZ, 20/10 approx. full load amps. -Three phase; 230V/460V, 60 Hz, 230V/460V, 60 Hz, 5.8/2.9 approx full load amps. RPM: 3450</p>	<p>08-02C3-X.75 1P .75 H.P. Single Phase</p>	<p>\$ 1,886.40</p>
	<p>08-02C3-X.75 3P .75 H.P. Three Phase</p>	<p>\$ 1,925.10</p>
	<p>08-02C3-X2 1P 2 H.P. Single Phase</p>	<p>\$ 2,503.80</p>
	<p>08-02C3-X2 3P 2 H.P. Three Phase</p>	<p>\$ 2,283.30</p>

GORMAN-RUPP ENGINE DRIVEN FUEL TRANSFER PUMPS

The safest way to approach any hazardous operation is to use a pump that's built to handle the job. Gorman-Rupp offers Shield-A-Spark pumps to transfer and deliver flammable liquids with peace of mind. Four Models are available in 2" and 3" discharge sizes.

Gorman-Rupp Model 82D1-XR550-X Self-Priming Centrifugal Pump Gasoline Engine Driven



Pump Specifications:

Size: 2" x 2" NPT - female
 Pump casing: Max operating pressure 50 psi.
 Semi-open type, three vane impeller: Handles 5/8" diameter spherical solids.
 Seal: Type 21, mechanical, self-lubricated. Carbon rotating face. Ni-resist stationary face.
 Fluorocarbon elastomers (viton or equivalent). Stainless steel type 18-8 cage and spring. Max temperature of liquid pumped, 160°



Engine Specifications:

Model: Briggs & Stratton XR550
 Type: Four cycle, air cooled, gasoline engine
 Full load operating time: 1.9 hours
 Starter: Rope Rewind
 Displacement: 13.4 Cu. In (219 cc)

Gorman-Rupp's Shield-A-Spark self priming pumps have spark and splashshielded engine, muffler and fuel fill cap. They also have spark plugs, ignition wire, sealed toggle ignition switch, approved spark-arrestor muffler, non-combustible air filter and long-life valves. This unit is designed to handle volatile, flammable liquids.

Standard Equipment Roll cage w/ rubber feet.
 90° discharge elbow (Shown)

Optional Equipment: Two Wheel kit assembly
 w/ semi-pneumatic tires.

MODEL #	PREFERRED
08-82D1-XR550-X	\$ 3,307.50

Gorman-Rupp Model 82D1-1B20FT4-X Self-Priming Centrifugal Pump Diesel Engine Driven



Pump Specifications:

Size: 2" x 2" NPT - female
 Pump casing: Max operating pressure 62 psi.
 Semi-open type, three vane impeller: Handles 5/8" diameter spherical solids.
 Seal: Type 1, mechanical, self-lubricated. Carbon rotating face. Ni-resist stationary face. Fluorocarbon elastomers (viton or equivalent). Stainless steel type 18-8 cage and spring. Max temperature of liquid pumped, 160°



**Up to 25' of suction lift
 Up to 200 GPM
 Depending on the application**

Engine Specifications:

Model: Hatz 1B20
 Type: Four cycle, air cooled, diesel engine
 Full load operating time: 1.8 hours
 Starter: Rope Rewind
 Displacement: 13.4 Cu. In (219 cc)

Gorman-Rupp's Shield-A-Spark self priming pumps have spark and splashshielded engine, muffler and fuel fill cap. They also have spark plugs, ignition wire, sealed toggle ignition switch, approved spark-arrestor muffler, non-combustible air filter and long-life valves. This unit is designed to handle volatile, flammable liquids.

Standard Equipment Roll cage w/ rubber feet.
 90° discharge elbow (Shown)

Optional Equipment: Two Wheel kit assembly
 w/ semi-pneumatic tires.

MODEL #	PREFERRED
08-82D1-1B30FT4-X	\$ 5,170.50

Gorman-Rupp Model 82E1-L100EFT4-X Self-Priming Centrifugal Pump Diesel Engine Driven



Pump Specifications:

Size: 3" x 3" NPT - female
 Pump casing: Max operating pressure 98 psi.
 Semi-open type, three vane impeller: Handles 3/4" diameter spherical solids.
 Seal: Type 1, mechanical, self-lubricated. Carbon rotating face. Ni-resist stationary face. Fluorocarbon elastomers (viton or equivalent). Stainless steel type 18-8 cage and spring. Max temperature of liquid pumped, 160°



**Up to 25' of suction lift
 Up to 200 GPM
 Depending on the application**

Engine Specifications:

Model: Yammer L100EE
 Type: Single cylinder, four cycle air cooled, diesel engine.
 Full load operating time: 2.1 hours
 Starter: Rope Rewind
 Displacement: 25.5 Cu. In (418 cc)

Gorman-Rupp's Shield-A-Spark self priming pumps have spark and splashshielded engine, muffler and fuel fill cap. They also have spark plugs, ignition wire, sealed toggle ignition switch, approved spark-arrestor muffler, non-combustible air filter and long-life valves. This unit is designed to handle volatile, flammable liquids.

Standard Equipment Roll cage w/ rubber feet.
 90° discharge elbow (Shown)

Optional Equipment: Two Wheel kit assembly
 w/ semi-pneumatic tires.

MODEL #	PREFERRED
08-82E1-L100WFT4-X	\$ 7,685.10

Gorman-Rupp Model 83A1-L100WFT4-X Self-Priming Centrifugal Pump Diesel Engine Driven



Pump Specifications:

Size: 3" x 3" NPT - female
 Pump casing: Max operating pressure 92 psi.
 Semi-open type, three vane impeller: Handles 3/4" diameter spherical solids.
 Seal: Type 1, mechanical, self-lubricated. Carbon rotating face. Ni-resist stationary face. Fluorocarbon elastomers (viton or equivalent). Stainless steel type 18-8 cage and spring. Max temperature of liquid pumped, 160°



**Up to 25' of suction lift
 Up to 380 GPM
 Depending on the application**

Engine Specifications:

Model: Yammer L100EE
 Type: Single cylinder, four cycle, air cooled, diesel engine.
 Full load operating time: 2.1 hours
 Starter: Rope Rewind
 Displacement: 25.5 Cu. In (418 cc)

Gorman-Rupp's Shield-A-Spark self priming pumps have spark and splashshielded engine, muffler and fuel fill cap. They also have spark plugs, ignition wire, sealed toggle ignition switch, approved spark-arrestor muffler, non-combustible air filter and long-life valves. This unit is designed to handle volatile, flammable liquids.

Standard Equipment Roll cage w/ rubber feet.
 90° discharge elbow (Shown)

Optional Equipment: Wheel kit assembly w/
 semi-pneumatic tires.

MODEL #	PREFERRED
08-83A1-L100WFT4-X	\$ 7,683.30



Leaders in Fluid Handling Solutions

Toll Free: 1-877-737-4690

www.strickequipment.com

J 6

NOTES

PLEASE USE THIS PAGE TO KEEP TRACK OF YOUR MOST POPULAR ITEMS ORDERED AND THEIR PART NUMBERS

A large, empty rectangular box with a black border, intended for handwritten notes or tracking of popular items and their part numbers.