

FILL CAPS & ADAPTORS

Vented Fill Cap	MODEL #	PREFERRED
 179	09-179-0100 2" Female	\$ 20.84
 179M	09-179-0300 3" Female	\$ 46.75
 179	09-179-0400 4" Female	\$ 60.52
 179CI	09-179CI-0100 2" Female Cast Iron	\$ 47.69
 179M	09-179M-0100 2" Male	\$ 22.61
 179MCI	09-179MCI-0100 2" Male Cast Iron	\$ 45.08
Pre-Vent Fill Cap	03-60001 PREVENT FILL CAP	\$ 21.79
 Combination Vent & Fill 2" Male NPT	03-60003 REPLACEMENT TOP	\$ 12.18
305 Fill Adaptor	09-305-0000 2"	\$ 63.64
 Adaptor is profile machined for cam and groove fit on industry standard tight seal caps.	09-305-0200 4"	\$ 75.88
305 C Fill Cap	09-305C-2000 2"	\$ 54.13
 4" Cap has center pull ring with toggle cam to fit adaptor groove. Tight seal and lockable. Powder-coat finish. 2" Cap has a single lever.	09-305C-0100 4"	\$ 57.88
Vapor Recovery	09-323C-0100-AC 4"	\$ 62.00
 Installed on Vapor Adaptors and Vapor Swivel Adaptors to prevent water and debris from entering the tank and prevent vapor from escaping when the adaptors are not in use. The cap has a tight seal and orange powder-coated finish.		

VENTS

	MODEL #	PREFERRED
354 Updraft Vent 	09-354-0100 1 1/2"	\$ 31.84
"Open" vent used on underground and aboveground tanks for motor fueling. Vent allows tank to "breath" during filling/dispensing operations.	09-354-0200 2"	\$ 27.39
	09-354-0300 3"	\$ 65.16
	09-354-0400 4"	\$ 144.03
155 "T" Style Vent 	09-155-0200AV 1 "	\$ 24.78
Aluminum T-style Vent used primarily on small fuel oil storage tanks. Outlet ports on either side of the inlet with 20 mesh stainless steel screen keeps debris out of the airway.	09-155-0400AV 1 1/2"	\$ 31.54
	09-155-0500AV 2"	\$ 37.94
Mushroom Vent Caps 	51-4021 3/4"	\$ 12.62
Rust-resistant galvanized cast iron design is available in female NPT sizes from 3/4" to 4" Each cap is designed with a 30 mesh screen, to prevent debris from entering the vent pipe.	51-4022 1"	\$ 16.37
	51-4023 1 1/4"	\$ 18.63
	51-4024 1 1/2"	\$ 22.64
	51-4025 2"	\$ 32.04
	51-4027 3"	\$ 101.95
	51-4028 4"	\$ 119.01

ANTI-SYPHON VALVES

			26-605-300-01 3/4"	\$ 624.84
Anti-Syphon Valve 		5' TO 12' HEAD PRESSURE	26-606-300-01 1"	\$ 642.62
-Thermal Expansion pressure relief valve -Automatically Shuts Flow Off When Lines are Broken -Each Valve has an Adjustable Head Pressure		12' TO 25' HEAD PRESSURE	26-616-300-01 1 1/2"	\$ 662.94
			26-636-300-11 2"	\$ 764.54
			26-616-300-02 1 1/2"	\$ 662.94
			26-636-300-12 2"	\$ 765.54

MORRISON EMERGENCY VENTS

244OM SERIES MALE THREADED CAST IRON E-VENTS



Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.

244O SERIES FEMALE THREADED CAST IRON E-VENTS



Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.

245M SERIES MALE THREADED ALUMINUM E-VENTS



Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.

245 SERIES FEMALE THREADED ALUMINUM E-VENTS



Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and rupturing if exposed to fire.

MODEL

PREFERRED

09-244OM-0020AV 2" MALE THREAD	\$ 86.46
09-244OM-0050AV 3" MALE THREAD	\$ 110.45
09-244OM-0100AV 4" MALE THREAD	\$ 130.84
09-244OM-0800AV 5" MALE THREAD	\$ 186.15
09-244OM-0200AV 6" MALE THREAD	\$ 200.65

09-244O-0100AV 4" FEMALE THREAD	\$ 124.95
09-244O-0200AV 6" FEMALE THREAD	\$ 182.12

09-245M-0300AV 3" MALE THREAD	\$ 87.35
09-245M-0400AV 4" MALE THREAD	\$ 105.35
09-245M-0600AV 6" MALE THREAD	\$ 159.89

09-245-0300AV 3" FEMALE THREAD	\$ 81.54
09-245-0400AV 4" FEMALE THREAD	\$ 98.48
09-245-0600AV 6" FEMALE THREAD	\$ 145.06

8" AND 10" E-VENTS AVAILABLE CALL FOR PRICING



Leaders in Fluid Handling Solutions

CALL US AT: 616-457-8782

www.strickequipment.com

F 4

AST SPILL CONTAINERS



**MORRISON 09-517
SPILL CONTAINER**

**3.5 GAL
AVAILABLE WITH MALE
OR FEMALE THREAD**

**Waste Oil Version
has screen**



**MORRISON 09-518
SPILL CONTAINER**

**7.5 GAL
AVAILABLE WITH MALE
OR FEMALE THREAD**

**Available in Center
or Offset Mounts**

	MODEL #	PREFERRED
	09-517-0100AC 2" 3.5 GAL. MALE THREADED	\$ 261.90
	09-517-0200AC 4" 3.5 GAL. MALE THREADED	\$ 288.25
	09-517F-0100AC 2" 3.5 GAL. FEMALE THREADED	\$ 272.97
	09-517F-0200AC 4" 3.5 GAL. FEMALE THREADED	\$ 303.72
	09-517WO-0100AC 2" 3.5 GAL. FEMALE THREADED W/ SCREEN	\$ 280.81
	09-518-0100AC 4" 7.5 GAL. FEMALE THREADS OFFSET MOUNT	\$ 600.20
	09-518CC-0100AC 4" 7.5 GAL. FEMALE THREADS CENTER MOUNT	\$ 600.20
	09-518M-0100AC 4" 7.5 GAL. MALE THREADS OFFSET MOUNT	\$ 600.20
	09-518M-0200AC 2" 7.5 GAL. MALE THREADS OFFSET MOUNT	\$ 576.84



Leaders in Fluid Handling Solutions

CALL US AT: 616-457-8782

www.strickequipment.com

F 5

SPILL CONTAINERS



15 Gallon AST Remote Spill Container

One, or Dual Fill Ports



EBW SPILL CONTAINERS



FLEX CATCH COVERS

MODEL #	PREFERRED
09-515-0200AC 2" 15 GAL FEMALE THREADED	\$ 1,599.34
09-515-0300AC 3" 15 GAL FEMALE THREADED	\$ 1,646.54
09-515-0400AC 4" 15 GAL FEMALE THREADED	\$ 1,671.59
09-515-2200AC 2" & 2" 15 GAL DUAL PORTS FEMALE THREADED	\$ 1,696.25
09-515-2300AC 3" & 3" 15 GAL DUAL PORTS FEMALE THREADED	\$ 1,828.17
26-705-470-01 5 GAL SPILL TRAP W/ DRAIN	\$ 1,079.50
26-705-409-00 ALUMINUM FLEX CATCH COVER	\$ 260.35
26-705-423-01 FIBER FLEX CATCH COVER	\$ 232.41
26-705-430-00 CAST IRON FLEX CATCH COVER	\$ 238.76



Leaders in Fluid Handling Solutions

TCALL US AT: 616-457-8782

www.strickequipment.com

F 6

OVERFILL, BY-PASS & PRESSURE RELIEF VALVES

		MODEL #	PREFERRED
	9095A	09-9095AA-3300AVEVR 3" OVERFILL ADAPTOR	\$ 1,587.11
	9095S	09-9095AA-0200AV 2" OVERFILL VALVE	\$ 1,347.58
		09-9095SA-0200AV 2" OVERFILL VALVE MALE	\$ 691.46
		09-078DI-0100AV 25 PSI SETTING	\$ 158.57
		09-078DI-0200AV 40 PSI SETTING	\$ 158.57
	1/2" EXPANSION RELIEF VALVES	09-078DI-0300AV 100 PSI SETTING	\$ 158.57
		09-174-0100AV 1 1/2" PSI STANDARD SETTING PRESSURE SETTINGS OF 30,40,50,60 & 75 PSI AVAILABLE AT ADDITIONAL CHARGE	\$ 432.09 CALL FOR PRICING
	09-174 BY-PASS VALVE 1 1/2" OR 2"	09-174-2200AV 2" 20 PSI STANDARD SETTING PRESSURE SETTINGS OF 30,40,50,60 & 75 PSI AVAILABLE AT ADDITIONAL CHARGE	\$ 466.35 CALL FOR PRICING

TANK GAUGES



Kreuger At-A-Glance Gauges

Direct mechanical action, reliable construction and "at-a-glance" readability make this gauge a perfect choice for tanks with depths up to 12'.

- Patented calibration assembly withstands pressure of 70 lbs. per sq. inch.
- Double plastic dome is almost indestructible.
- "Gallon" readout available for Standard 275 Gallon Oval Tanks.
- All "internal tank" parts available in stainless steel or plastic.
- Repair parts available.

TANK DEPTH	MODEL #	PREFERRED
27"	12-D-1.5-27 1 1/2"	\$ 34.57
	12-D-2-27 2"	\$ 34.57
38"	12-D-1.5-38 1 1/2"	\$ 34.57
	12-D-2-38 2"	\$ 34.57
44"	12-D-1.5-44 1 1/2"	\$ 34.57
	12-D-2-44 2"	\$ 34.57
48"	12-D-1.5-48 1 1/2"	\$ 41.61
	12-D-2-48 2"	\$ 41.61
60"	12-D-1.5-60 1 1/2"	\$ 41.61
	12-D-2-60 2"	\$ 41.61
64"	12-D-1.5-64 1 1/2"	\$ 51.96
	12-D-2-64 2"	\$ 51.96
Krueger At-A-Glance replacement tops	12-DCAL	\$ 8.83
Krueger At-A-Glance repair kits - includes top, red nut, gasket, indicator disc	12-DKIT	\$ 15.88
Krueger At-A-Glance Glass insert replacement	12-DG-CAL	\$ 18.23
Krueger Glass gauge repair kits - include glass insert, red nut & gasket, & red indicator	12-DG-KIT	\$ 23.25

INTERSTITIAL LEAK GAUGE



Krueger Leak Gauges

Vertical type leak monitor used for detecting leaks in the annular/interstitial space of a double wall above ground tank.

TANK DEPTH	MODEL #	PREFERRED
UP to 48"	12-K-1.5-48	\$ 72.58
UP to 38"	12-K-2-38	\$ 64.45
UP to 48"	12-K-2-48	\$ 72.58
UP to 64"	12-K-2-64	\$ 72.58
UP to 108"	12-K-2-108	\$ 105.18
Leak Gauge Top	12-KCAL	\$ 8.83
Leak Gauge Kit	12-KKIT	\$ 18.55

KRUEGER H TYPE GAUGES & KING GAUGES

Krueger Type H Therma Gauges



The therma Type H gauge is a reliable, swing arm type tank gauge. The difference from an At-A-Glance gauge and Type H gauge is the bushing. This gauge has an easily removable bushing which allows you to thread the bushing into the tank first. This eliminates the swing arm from spinning inside the tank and allows you to aim the swing arm where you want it.

* Galvanized Construction
* HDPE Floats
* Aluminum body

Tank Depth	MODEL #	PREFERRED
30"	12-H-2-30 2"	\$ 39.74
38"	12-H-2-38 2"	\$ 39.74
44"	12-H-1.5-44 1 1/2"	\$ 39.74
	12-H-2-44 2"	\$ 39.74
46"	12-H-2-46 2"	\$ 39.74
48"	12-H-1.5-48 1 1/2"	\$ 47.54
	12-H-2-48 2"	\$ 47.54
60"	12-H-2-60 2"	\$ 47.54
64"	12-H-1.5-64 1 1/2"	\$ 58.86
	12-H-2-64 2"	\$ 58.86

Type H Therma Gauge replacement top

12-HCAL \$ 8.83

Krueger Type H repair kits - includes top, red lock nut, gasket & indicator disc

12-HKIT \$ 16.93

Krueger At-A-Glance Alarm



Loud Audible alarm (102 dB)
Easy installation
Set for high level, low level or leak detection alarm
Lithium battery
Can add on to existing gauges
Weather resistant convenient reset switch

12-DALARM \$ 144.00

King Gauges



The King gauge is made entirely of rustproof materials. Resin treated float is unaffected by oil or moisture condensation and simple lever action assures trouble free operation. Gauge has 1 1/2" and 2" threads for versatile use with any size tank opening.

51-4504
44" \$ 37.44

51-4490A-38
38" \$ 48.67

51-4490A-48
48" \$ 48.67

51-4490A-64
64" \$ 48.67

King Gauge Top w/ Gasket

51-4495 \$ 6.79



Leaders in Fluid Handling Solutions

CALL US AT: 616-457-8782

www.strickequipment.com

F 9

VENT ALARMS & GAUGES

	KING COMBINATION ALARM/GAUGE	MODEL #	PREFERRED
		51-4522 1 1/2" x 1 1/4"	\$ 56.24
	Nitrophyl Float is impervious to petroleum products Tangle-Free "Solid Link" hinge withstands rough handling. Durable cast iron with corrosion-resistant powder coating. Available to fit both Vertical and Horizontal tank applications. Large, easy-to-read, plastic vial includes UV inhibitors and is break-resistant. First size indicates bottom thread size Second size indicates top thread size	51-4523 2" x 1 1/4"	\$ 56.24
		51-4524 1 1/2" x 1 1/2"	\$ 56.24
		51-4525 2" x 1 1/2"	\$ 56.24
		51-4526 2" x 2"	\$ 66.16
	HORIZONTAL TANKS 26"-27" First size indicates bottom thread size Second size indicates top thread size	Horizontal 51-4531 1 1/2" x 1 1/2"	\$ 56.24
	KING FILL ALARMS Sizes to fit most popular above-ground and in-ground tanks Durable cast iron with corrosion-resistant powder coating Whistles while tank is being filled; stops whistling when oil has reached safe capacity level.	51-4509 1 1/4" x 1 1/4"	\$ 34.74
		51-4511 1 1/2" x 1 1/4"	\$ 34.74
	Industry's widest range of male and female NPT sizes. Available in sizes from 1 1/4" x 1" to 2" x 2"	51-4512 1 1/2" x 1 1/2"	\$ 34.74
		51-4514 2" x 1 1/4"	\$ 34.74
		51-4515 2" x 1 1/2"	\$ 34.74
		51-4517 2" x 2"	\$ 62.51
	Morrison Bros. Co. Established 1855	09-818-0100AGEVR Clock Gauge	\$ 618.74
818 Clock Gauge	For Measuring liquid level in aboveground storage tanks. Gauge mounts on top of tank and is activated by a float connected to a cable. Readout is on a 1 hour clock face. Small hand=feet, Large hand=inches. Gauge can be read 20-30 feet away. Maximum measurement is 12 feet.		
	Utilizes the 818 clock gauge with a built-in high level warning alarm. Contains a battery powered, intrinsically safe alarm unit that is mounted in a remote location. Alarm level is set during installation and can be reset at any time.	09-918C-0100AG Clock Gauge w/ Alarm	\$ 1,391.76

OPW TANK GAUGES

OPW 200TG TANK GAUGE

The OPW200TG tank gauge is designed for reading liquid levels in horizontal vertical aboveground storage tanks. It provides an accurate numerical counter readout, eliminating the need for any on-site manual gauging. Fits up to a 40' tank. UL Listed.



MODEL #	PREFERRED
28-200TG- ENG18 UP to 18'	\$ 761.45
28-200TG- ENG40 UP to 40'	\$ 898.52

FEATURES:

- * **Vapor Tight:** Allows for standard tank pressure testing, sealing up to 25 PSIG.
- Angled Face:** Improves visibility from ground on large diameter tanks. May be read easily up to 30' away.
- Swivel Adaptor Base:** Allows 360° gauge face rotation for easy viewing wherever needed.
- Easy Installation:** 2" NPT threaded base reduces labor time and comes standard with female thread. A 200-0202 may be purchased for male thread applications.
- * **Corrosion-Resistant Construction:** A powder coated die-cast aluminum body ensures long service life in many fluids.
- * **Float Buoyancy:** Designed to float in all fluids with a specific gravity of 0.65 or greater.
- * **Unit Measurement:** Can be purchased in metric units to read in meters, 1/10, 1/100, or english units to read in feet and inches accurate to 1/8'.
- * **Maintenance:** No annual maintenance required.
- * **Tank Size:** Available in either 18' or 40' tank depths.
- * **Drop Tube:** Prevents float entanglement in the tank and gives the gauge a more accurate reading when turbulence is present. **(SOLD SEPARATELY).**

OPW 144TA LIQUID LEVEL TANK ALARM

The 144TA Tank Alarm is designed for one tank. The 444TA is designed for four tanks. Both have high or low liquid level sensing in liquid tanks. Both audio and visual indicators are used to ensure reliable notifications. Both the 144TA and the 444TA require the 44TA-LLFS liquid level float switch.



FEATURES:

- * **Long Life Lithium Battery:** Self powered by a Lithium battery; includes a 10 year shelf life to ensure peace of mind for the owner.
- * **Visual Notifications:** Red alarm light flash during use for notification to the user. Low battery light indicates when battery needs replacing.
- * **Audible Alarm:** Sounds a 90 decible alarm at 4' away to meet OSHA requirements.
- * **Active from the time it leaves the factory:** There is no on/off switch to deal with which means no drained batteries and operator error are eliminated.
- * **Stainless Steel Pipe Construction:** Allows use in any array of fluid applications.
- * **Easy Installation:** Requires no calibration and installs easily into a 1" bung.
- * **Cold Weather Applicable:** All components are rated for -40°F operation.

MODEL #	PREFERRED
28-144TA-0100	\$ 727.84
28-444TA-0100	\$ 1,097.63
28-44TA-LLFS	\$ 338.74

**SWING CHECK VALVES, EXTERNAL EMERGENCY VALVES, IMPACT VALVES,
& PRESSURE REGULATOR VALVES**
SWING CHECK VALVES

DIXON SWCV
 Swing Check
 Valve
 Brass

MORRISON 246A
 Swing Check
 Valve
 Body - Brass
 Gasket - Nitrile

MODEL #		PREFERRED
06-SWCV50	1/2"	\$ 18.10
06-SWCV75	3/4"	\$ 23.10
06-SWCV100	1"	\$ 31.45
06-SWCV125	1 1/4"	\$ 52.99
09-246A-0100AV	1 1/2"	\$ 285.24
09-246A-0200AV	2"	\$ 300.31
09-246A-0400AV	3"	\$ 520.65

FARM TANK EMERGENCY VALVES

Farm Tank Emergency Valve

Angle Style, Furnished with 160° fusible link. All brass construction.

09-474-0100
 1" x 3/4" NPT

09-474-0200
 1" x 1" NPT

Farm Tank Emergency Valve

Straight Style, Furnished with 160° fusible link. All brass construction.

09-574-0100AV
 1" x 1" NPT

DUPLEX & DOUBLE TAPPED BUSHINGS
DOUBLE TAPPED BUSHINGS


Cast Iron with NPT Threads

Other Sizes Available
09-184-0200
 2" x 1/2"

09-184-0300
 2" x 3/4"

09-184-0400
 2" x 1"

09-184-0600
 2" x 1 1/2"

09-184-1200
 3" x 1 1/2"

09-184-1400
 3" x 2"

09-184-2400
 4" x 1 1/2"

09-184-2500
 4" x 2"

DUPLEX BUSHINGS

2" Male NPT for aboveground or underground installations. Fittings available for 3/8", 1/2" copper tubing.

09-184D-0100
 2"x3/8"x3/8"

09-184D-0200
 2"x1/2"x1/2"

09-184D-0300AB
 4"x3/4"x3/4"

\$ 131.04



Leaders in Fluid Handling Solutions

CALL US AT: 616-457-8782

www.strickequipment.com

F 12

GATE, BALL, AND SOLENOID VALVES

Lockable & Non-Lockable Gate Valves



Rising Stem Gate Valve used for manual flow control in petro-chemical liquid handling. Available in brass and ductile iron. This gate valve operates by rotating handwheel counter-clockwise to open or clockwise to close. Valve can be left partially open to control flow rate. Cold non-shock pressure limit of 200 psi. Available with standard Buna seals or with Teflon seals.



FULL PORT BALL VALVES

Full port ball valve used for liquid handling with manual open-close in quick quarter-turn handle operation. Threaded (NPT) connections. Valve can be operated in partial or open position. B0series is Lockable with padlock.



Solenoid Valves

- Explosion Proof
- 110 Volt
- Used to prevent accidental siphoning
- 2 way, 1 directional
- Normally closed

	MODEL #	PREFERRED
NON-LOCKABLE	09-235-0200 2"	\$ 438.40
	09-235-0400 3"	\$ 648.16
LOCKABLE	09-235B-0200 2"	\$ 507.15
	09-235B-0400 3"	\$ 735.10
NON-LOCKABLE	09-691-0300 1/2" Std	\$ 16.16
	09-691-0400 3/4" Std	\$ 23.04
	09-691-0500 1" Std	\$ 37.64
	09-691-0700 1 1/2" Std	\$ 73.91
	09-691-0800 2" Std	\$ 121.71
	09-691-1000 3" Std	\$ 466.22
	09-691B-0300 1/2" Lockable	\$ 20.97
	09-691B-0400 Lockable	\$ 28.37
LOCKABLE	09-691B-0500 1" Lockable	\$ 42.99
	09-691B-0700 1 1/2" Lockable	\$ 79.77
	09-691B-0800 2" Lockable	\$ 127.56
	09-691B-1000 3" Lockable	\$ 482.90
	09-710-0075 3/4"	\$ 689.31
	09-710-0100 1"	\$ 887.13
	09-710-0150 1 1/2"	\$ 1,088.81
	09-710-0200 2"	\$ 1,329.45
	09-710-0300 3"	\$ 3,668.52

LINE STRAINERS

CAST IRON Y LINE STRAINER	MODEL #	PREFERRED
	06-Y004 3/4"	\$ 63.26
Cast iron body, female x female NPT ends, 304 stainless steel strainer, graphite gasket, 400 PSI WOG, 200 PSI working steam pressure.	06-Y005 2"	\$ 78.91
	06-Y006 1 1/4"	\$ 111.76
	06-Y007 1 1/2"	\$ 137.62
	06-Y008 2"	\$ 206.52
	09-285 1 1/2" THREADED	\$ 161.39
Bottom Clean-Out Y-type strainer used in pipelines to filter debris from flowing into and damaging equipment such as a pump or a meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the bottom. Cast iron body and cap, malleable iron yolk, 304 stainless strainer. Threaded (NPT) connections. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.	09-285 2" THREADED	\$ 196.63
	09-285 3" THREADED	\$ 323.74
	09-285FDI 3" FLANGED	\$ 903.41
Bottom Clean-Out Y-type strainer used in pipelines to filter debris from flowing into and damaging equipment such as a pump or a meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the bottom. Has a 150# raised flanged connections, ductile iron body and cap. Companion flanges available. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.		
	09-286 2" THREADED	\$ 348.91
Top Clean-Out Y-type strainers are used in pipelines to filter out debris from flowing into and damaging equipment such as a pump or meter. Strainer basket is removable for cleaning and/or replacement. Basket access is from the top. Cast iron body and cap, malleable iron yolk. Threaded (NPT) connections. Available in 6, 10, 20, 40, 60, 80, and 100 Mesh.	09-286 3" THREADED	\$ 622.25
	09-286FDI 3" FLANGED	\$ 1,122.27

BARREL FAUCETS & ACCESSORIES

	MODEL #	PREFERRED
	09-215A-0100 3/4" NPT	\$ 53.63
Oil & Molasses Valves For Heavy Oils or Liquids Body - Iron Gate - Brass	09-215A-0500 2" NPT	\$ 77.60
	09-110-0200 3/4" NPT	\$ 120.03
Quick Closing Barrel Faucets Available in 3/4" or 1" Male NPT Standard Disc is Buna; Teflon and Viton available at additional charge.	09-110-0300 1" NPT	\$ 138.44
	09-633-0500 1" x 1" NPT	\$ 61.22
	09-699F-0400 3/4" X 3/4" NPT	\$ 52.97
Barrel Faucets Ball Valve Type Faucet Style Quarter Turn All Brass Body	09-699F-0500 1" X 1" NPT	\$ 74.38
	15-ZE68SP 3/4" NPT	\$ 4.12
Plastic Bung Faucets for 3/4" & 2" NPT bung openings.	15-ZE67 2" NPT	\$ 22.85
	15-ZE81 3/4" NPT	\$ 15.02
Die-cast metal bung faucet for 3/4" NPT bung opening in steel drums or barrels. Self-closing. Has hole for padlock.		
	15-ZE830	\$ 40.02
Brass Drum Vent 2" NPT. For petroleum based applications.		
	15-ZE169	\$ 17.96
Non-Sparking aluminum wrench for use with 2" and 3/4" drums.		



Leaders in Fluid Handling Solutions

CALL US AT: 616-457-8782

www.strickequipment.com

F 15

NOTES

PLEASE USE THIS PAGE TO KEEP TRACK OF YOUR MOST POPULAR ITEMS ORDERED AND THEIR PART NUMBERS